

Facestock

A white, one side machine coated, woodfree printing paper with semi-gloss appearance.

Basis Weight	80 g/m²	ISO 536
Caliper	69 µm	ISO 534

Adhesive

FR8 is a transparent, dispersion-based permanent, acrylic adhesive.

Liner

BG40 brown, a supercalendered glassine paper.

Basis Weight	58 g/m²	ISO 536
Caliper	51 µm	ISO 534
Laminate		
Total Caliper	140 µm±10%	ISO 534
Performance data		
Initial Tack	7 N/25mm	FTM 9 Glass
Peel Adhesion 90°	6 N/25mm	FTM 2 St.St.
Min. Application Temp.	-20 °C	
Service temperature	-50°C to 80°C	

Adhesive Performance

FR8 has been specially developed for deep-freeze applications preferably below 15°C. The labelling of refrigerated products and products at room temperature is likewise possible, provided that they are immediately deep-frozen after labelling (shockfrozen to approx. -35°C). The best adhesion is obtained at subzero temperatures (maximum adhesion is obtained at -15°C), whereby care must be taken to ensure complete absence of ice on the surface.

Applications and use

The product is suitable for a wide range of promotional and industrial label applications where attractive semi-gloss appearance in multi-colour work is required.

Conversion & printing

Facestock is suitable for solid and halftone images and text printing by letterpress, flexo (UV and waterbased) offset and screen processes. Hot and cold foil stamping, varnishing and variable imprinting with thermal transfer are also suitable for this product.


Special Approvals

The adhesive complies with the European food directives and legislations, the German recommendations XIV as published by BfR. BfR (Bundesinstitut für Risikobewertung) is the German Federal Institute for Risk Assessment. The adhesive can be used in direct contact with dry and wet, non fatty foodstuffs.

Shelf life

Half a year under storage conditions as defined by FINAT (20-25°C; 40-50%RH)

AA255 Fasson ® MC PRIMECOAT - FR8-BG40BR



MC PRIMECOAT

FR8

BG40BR



Inspired Brands. Intelligent World."

Avery Dennison Materials Group Europe

Lammenschansweg 140 2321 JX Leiden The Netherlands +31 71 579 4100



This is an automatically generated datasheet. All data to be considered as typical values and subject to change without prior notice. Further testing is always recommended.

If you would like to make a suggestion or report a mistake on this datasheet, please send an email to datasheet.mgmt@eu.averydennison.com Warranty

All Avery Dennison statements, technical information and recommendations are based ANY OTHER WARRANTY, WHETHER EXPRESS OR IMPLIED, OR WHETHER OF on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR OTHERWISE, Dennison products are sold with the understanding that purchaser has independently SHALL BE EXCLUDED. NO WAIVER, ALTERATION, ADDITION OR MODIFICATION determined the suitability of such products for its purposes

Avery Dennison products are warranted to be free of defects in material or workmanship for a period of one year from the date of shipment. Should a defect be ©2013 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other communicated to Avery Dennison within that time frame, Avery Dennison will evaluate Avery Dennison brands, this publication, its content, product names and codes are and determine the existence of the defect and further decide, at its sole discretion, to owned by Avery Dennison Corporation. All other brands and product names are either replace the defective product without charge or compensate it with a credit note trademarks of their respective owners. This publication must not be used, copied or in such amount as Avery Dennison deems reasonable. Avery Dennison shall have no reproduced in whole or in part for any purposes other than marketing by Avery responsibility beyond the replacement value of the defective product nor shall in any Dennison. way be liable or responsible for consequential or incidental damages.

OF THE FOREGOING CONDITIONS SHALL BE VALID UNLESS MADE IN WRITING AND SIGNED BY AN EXECUTIVE OFFICER OF AVERY DENNISON.