

Facestock

A gloss white polyester film. The smooth surface is covered with a topcoat for very good ink anchorage.

Basis Weight	76 g/m ²	ISO 536
Caliper	50 µm	ISO 534

Adhesive

R8514 is a solvent based acrylic ultraremovable adhesive.

Liner

BG40 white, a supercalendered glassine paper.

Basis Weight	60 g/m ²	ISO 536
Caliper	53 µm	ISO 534

Laminate

Total Caliper	119 µm±10%	ISO 534
---------------	------------	---------

Performance data

Initial Tack	3 N/25mm	FTM 9 Glass
Peel Adhesion 90°	1 N/25mm	FTM 2 St.St.
Min. Application Temp.	0 °C	
Service temperature	-40°C to 150°C	
Adhesive Type	solvent acrylic	

Adhesive Performance

The adhesive R8514 combines good anchorage to the face material with excellent cohesion leading to clean and residue free removability from materials used for the production of electronic equipment as well as domestic appliances.

Applications and use

Transfer PET white TOP white is designed for conversion into identification, warning and tracking labels for durable goods such as automotive parts, electronic devices and home appliances.

This product is distinguished by the high chemical resistance of the thermal transfer print. For special requirements we strongly recommend application tests.

Due to the clean removability from a wide range of substrates - also after the exposure to different temperatures - this is a superior product for the conversion into point-of-sales labels. The liner is made from FSC® certified paper (FSC Mix Credit, chain-of-custody number: CU-COC-807907, Licence Code: C004451).

Conversion & printing

Very good results can be achieved with thermal transfer printers equipped with conventional or near-edge print heads using resin ribbons. Transfer PET white TOP can also be printed by all conventional roll label techniques, including flexo, UV letterpress, silkscreen. This material is qualified for UV inkjet printing by the following printer manufacturers: EFI Jetrion, Domino (n610i), Durst (TAU 330 RSC) and Xeikon (PX3000). Results of durability tests are available on request. For easy diecutting sharp corners should be avoided.


Shelf life

Two years under storage conditions as defined by FINAT (20-25°C; 40-50%RH)

AM663

Fasson®

TRANSFER PET WHITE TOP - R8514-BG40WH FSC



TRANSFER PET WHITE TOP

R8514

BG40WH FSC

This is an automatically generated datasheet. All data to be considered as typical values and subject to change without prior notice. The actual front and liner used might influence adhesive values. Further testing is always recommended.

If you would like to make a suggestion or comment on this datasheet, please send an email to datasheet.mgmt@eu.averydennison.com

Willem Einthovenstraat 11
2342 BH Oegstgeest
The Netherlands
+31 (0)85 000 2000



Warranty

All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>

©2019 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.