

**AR232****Fasson ®
TRANSF PET MATT CHR
TOP - S8001-BG42WH
BSS**

Key features

- > Excellent TT printability.
- > UL and CSA recognised label material.

> Acrylic adhesive offering high tack and peel adhesion on a wide variety of substrates, including low surface energy plastics.

Facestock

A matt finished metallic polyester film. The smooth surface is covered with a topcoat for excellent ink anchorage.

Basis Weight	65 g/m ²	ISO 536
Caliper	50 µm	ISO 534

Adhesive

S8001 is a permanent acrylic adhesive with good initial tack and high ultimate adhesion onto a variety of substrates including apolar plastics and lacquers.

Liner

BG42Wh BSS: on both sides siliconized glassine paper, wood-free, super calandered and extremely tough and tear-resistant despite its thinness.

Basis Weight	64 g/m ²	ISO 536
Caliper	55 µm	ISO 534
Transparency	45 %	DIN 53147

Laminate

Total Caliper	132 µm±10%	ISO 534
---------------	------------	---------

Performance data

Initial Tack	15 N/25mm	FTM 9 Glass
Min. Application Temp.	5 °C	
Service temperature	-40°C to 150°C	
Peel Adhesion 90°	9 N/25mm	FTM 2 st.st. 24hr

Adhesive Type	Emulsion Acrylic
---------------	------------------

Adhesive Performance

S8001 offers good resistance to solvents and cleaners. The adhesive has a high cohesion and can be used for labelling curved or round substrates.

Applications and use

Transfer PET matt chrome TOP was specially developed for industrial labels and thermal transfer applications. Thanks to the special surface coating, excellent results can be achieved with thermal transfer printers equipped with conventional or near-edge print heads using resin ribbons.

S8001 is specifically developed for labelling electronic, home appliance and other electrical items due to its good bonding performance on a wide range of polar and apolar surfaces including metals, polycarbonate, ABS and polypropylene. S8001 is available worldwide meaning it is suitable for global manufacturers seeking to consolidate label specifications around the world.


Conversion & printing

This product is qualified by EFI Jetrion and Durst for UV inkjet printing. In addition to thermal transfer printing the film can also be printed by all conventional roll label techniques, such as flexo, UV letterpress, silkscreen. Specific testing is required. For easy diecutting sharp corners should be avoided.

The backside siliconisation of the liner aids the conversion of this material as it reduces the risk of labels transferring to the backside of the label stock after diecutting.

AR232

Fasson ® TRANSF PET MATT CHR TOP - S8001-BG42WH BSS



TRANSF PET MATT
CHR.TOP

S8001

BG42WH BSS

UL and CSA Recognitions

This product meets the requirements as stated in UL 969 and CSA C22.2 No. 0.15 for indoor and outdoor use. The UL file number is MH27538.

Shelf life

Two years under storage conditions as defined by FINAT (20-25°C; 40-50%RH)

All data to be considered as typical values and subject to change without prior notice. Further testing is always recommended.

If you would like to make a suggestion or comment on this datasheet, please send an email to datasheet.mgmt@eu.averydennison.com

Avery Dennison Materials Group Europe

Willem Einthovenstraat 11
2342 BH Oegstgeest
The Netherlands
+31 (0)85 000 2000

Warranty

All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>



©2016 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.