

Facestock

A white coated, woodfree printing paper with semi-gloss appearance, laminated to a flexible aluminium barrier foil.

Basis Weight	81 g/m ²	ISO 536
Caliper	64 µm	ISO 534

Adhesive

A special purpose permanent, rubber based adhesive.

Liner

BG50 white, a supercalendered glassine paper.

Basis Weight	78 g/m ²	ISO 536
Caliper	68 µm	ISO 534

Laminate

Total Caliper	171 µm±10%	ISO 534
---------------	------------	---------

Performance data

Initial Tack	45 N/25mm	FTM 9 Glass
Peel Adhesion 90°	25 N/25mm	FTM 2 St.St.
Min. Application Temp.	0 °C	
Service temperature	-20°C to 70°C	

Adhesive Performance

TS79 is specially designed to meet the performance requirements of automotive tyre labelling. The special composition provides a superb anchorage of the label to the compound curved and extremely irregular surface of tyres, neglecting the negative influences of surface contaminants such as mould release agents or components migrating from the rubber.

This label material does not have any negative effect on the properties and performance of labelled tyres.

Note: this product contains a very aggressive adhesive. If the product is without SGP (Special Gum Pattern), slitreels will not be delivered with bleed-free edges and edge-bleed can occur. In case bleed-free edges are required, please contact your local sales representative.

Applications and use

For track and trace purposes in the tyre industry.



Shelf life

One year under storage conditions as defined by FINAT (20-25°C; 40-50%RH)

AA875

Fasson®

TYRE PLUS - TS79-BG50 WH IMP



This is an automatically generated datasheet. All data to be considered as typical values and subject to change without prior notice. The actual front and liner used might influence adhesive values. Further testing is always recommended.

If you would like to make a suggestion or comment on this datasheet, please send an email to datasheet.mgmt@eu.averydennison.com

Avery Dennison Materials Group Europe

Willem Einthovenstraat 11
2342 BH Oegstgeest
The Netherlands
+31 (0)85 000 2000

Warranty

All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>



©2019 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.



Inspired Brands.
Intelligent World.™