

Facestock

A matt white, ultra-destructible PEHD film with print-receptive surface.

Basis Weight	60 g/m ²	ISO 536
Caliper	109 µm	ISO 534

Adhesive

An extra permanent, acrylic based adhesive.

Liner

BG45 white, a supercalendered glassine paper.

Basis Weight	73 g/m ²	ISO 536
Caliper	62 µm	ISO 534
Transparency	50 %	DIN 53147

Laminate

Total Caliper	197 µm±10%	ISO 534
---------------	------------	---------

Performance data

Initial Tack	20 N/25mm	FTM 9 Glass
Peel Adhesion 90°	12.5 N/25mm	FTM 2 St.St.
Min. Application Temp.	5 °C	
Service temperature	-40°C to 90°C	

Adhesive Performance

S700 is a reinforced permanent acrylic based adhesive with very good initial tack and adhesion to a wide range of substrates.

Applications and use

This film is ultra-destructible by de-lamination. Combined with the high adhesive performance, this fragility will give a rapid 'tamper evident' bond on most substrates which creates an ideal security feature. Because these characteristics can limit label relocation, an application pre-test is advisable to determine suitability.

Conversion & printing

The product can be printed by all conventional printing technologies including water-based flexo, letterpress and UV-screen and thermal transfer. It is recommended that corners are designed with as large a radius is practical to facilitate matrix stripping.

Rolls must be handled with care during slitting, transport and storage to avoid edge damage.


Shelf life

Two years under storage conditions as defined by FINAT (20-25°C; 40-50%RH)

AB079

Fasson®

PE HD TAMPEREVIDENT - S700-BG45WH



PE HD TAMPEREVIDENT

S700

BG45WH

This is an automatically generated datasheet. All data to be considered as typical values and subject to change without prior notice. The actual front and liner used might influence adhesive values. Further testing is always recommended.

If you would like to make a suggestion or comment on this datasheet, please send an email to datasheet.mgmt@eu.averydennison.com

Avery Dennison Materials Group Europe

Willem Einthovenstraat 11
2342 BH Oegstgeest
The Netherlands
+31 (0)85 000 2000

Warranty

All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see



©2019 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery

