

Facestock

A white, machine coated semi-gloss printing paper, chemically treated to provide a barrier against oil and greases. The facestock is made with FSC certified pulp (FSC Mix Credit, chain-of-custody number: CU-COC-807907)

Basis Weight	90 g/m ²	ISO 536
Caliper	84 µm	ISO 534

Adhesive

A special purpose permanent, acrylic based adhesive for direct food contact.

Liner

BG40 white, a supercalendered glassine paper.

Basis Weight	63 g/m ²	ISO 536
Caliper	55 µm	ISO 534

Laminate

Total Caliper	160 µm±10%	ISO 534
---------------	------------	---------

Performance data

Initial Tack	10 N/25mm	FTM 9 Glass
Peel Adhesion 90°	6.5 N/25mm	FTM 2 St.St.
Min. Application Temp.	-15 °C	
Service temperature	-50°C to 70°C	

Applications and use

Special care should be given during dispensing around the gum free area

Conversion & printing

The specially treated face material can be printed by letterpress, flexo, gravure, screen and hot foil stamping. The special product lay-out could have an influence on conversion speed

Special Approvals




S2800 complies with European food regulation 1935/2004/EC, with the German Recommendation (BfR) XIV and with FDA § 175.105. It also meets the demands of the limit values laid down in 10/2011/EU. In accordance with the requirements of relevant EU food regulations, the adhesive S2800 may safely stand in direct contact with dry, moist and fatty foodstuffs which have a reduction factor of at least 2 according to the Commission Regulation (EU) No 10/2011.

Shelf life

Two years under storage conditions as defined by FINAT (20-25°C; 40-50%RH)

AC040

Fasson® TECOAT N - S2800 INC SGP- BG40WH



Avery Dennison Materials Group Europe

Lammenschansweg 140
 2321 JX Leiden
 The Netherlands
 +31 71 579 4100



This is an automatically generated datasheet. All data to be considered as typical values and subject to change without prior notice. Further testing is always recommended.

If you would like to make a suggestion or report a mistake on this datasheet, please send an email to datasheet.mgmt@eu.averydennison.com

Warranty

All Avery Dennison statements, technical information and recommendations are based ANY OTHER WARRANTY, WHETHER EXPRESS OR IMPLIED, OR WHETHER OF



Inspired Brands.
Intelligent World.™

on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes.

Avery Dennison products are warranted to be free of defects in material or workmanship for a period of one year from the date of shipment. Should a defect be communicated to Avery Dennison within that time frame, Avery Dennison will evaluate and determine the existence of the defect and further decide, at its sole discretion, to either replace the defective product without charge or compensate it with a credit note in such amount as Avery Dennison deems reasonable. Avery Dennison shall have no responsibility beyond the replacement value of the defective product nor shall in any way be liable or responsible for consequential or incidental damages.

MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR OTHERWISE, SHALL BE EXCLUDED. NO WAIVER, ALTERATION, ADDITION OR MODIFICATION OF THE FOREGOING CONDITIONS SHALL BE VALID UNLESS MADE IN WRITING AND SIGNED BY AN EXECUTIVE OFFICER OF AVERY DENNISON.

©2013 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.