

Facestock

A white, wet strength cast coated, mirror finished wood free printing paper. The facestock is made from FSC® certified paper (FSC Mix Credit, chain-of-custody number: CU-COC-807907, Licence Code: C004451).

Basis Weight	80 g/m ²	ISO 536
Caliper	84 µm	ISO 534

Adhesive

WLA is a transparent, dispersion-based permanent, acrylic adhesive.

Liner

BG45 white FSC is a supercalendered glassine paper.

Basis Weight	70 g/m ²	ISO 536
Caliper	61 µm	ISO 534

Laminate

Total Caliper	161 µm±10%	ISO 534
---------------	------------	---------

Performance data

Initial Tack	18 N/25mm	FTM 9 Glass
Peel Adhesion 90°	7 N/25mm	FTM 2 St.St.
Min. Application Temp.	10 °C	
Service temperature	-20°C to 80°C	

Adhesive Performance

WLA permits residue-free removal of bottle labels when washed in an alkali solution. It is ideal for the labelling of returnable bottles.

Applications and use

The product is suitable for primary labelling of high and luxury goods with a traditional image, eg : wines, spirits and specialist foods.

It is recommended to use an alkaline solution with 1.5% lye, with a min. temperature of 80°C for the bottle washing. The removability is substantially influenced by the wash off temperature (the higher the temperature, the shorter the wash off time), by the type of paper used, by the kind of print (line or halftone varnished or laminated) and the storage and weathering of applied label. As these are factors outside Avery Dennison control, we cannot guarantee trouble free removal in every possible application. It is therefore absolutely essential that the printed label be checked for the removability under the actual conditions of use. The use of non permeable faces is not recommended as these faces will result in a poor washability function.

The liner is made from FSC® certified paper (FSC Mix Credit, chain-of-custody number: CU-COC-807907, Licence Code: C004451).

Conversion & printing

Cast coated paper is especially suitable for best quality letterpress, offset print and small font text printing due to its smooth surface. Due to the closed surface of these products inks should be carefully validated for these products.


Shelf life

Two years under storage conditions as defined by FINAT (20-25°C; 40-50%RH)

AC461

Fasson ®

HGWINE PREMIUM FSC - WLA-BG45WH



HGWINE PREMIUM FSC

WLA

BG45WH FSC

This is an automatically generated datasheet. All data to be considered as typical values and subject to change without prior notice. Further testing is always recommended.

If you would like to make a suggestion or comment on this datasheet, please send an email to datasheet.mgmt@eu.averydennison.com

Avery Dennison Materials Group Europe

Willem Einthovenstraat 11
2342 BH Oegstgeest
The Netherlands
+31 (0)85 000 2000

Warranty

All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>



©2016 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.