

### Facestock

A matt, white woodfree machine finished paper with good opacity, excellent absorption and superior toner bonding characteristics. The facestock is made with FSC certified pulp (FSC Mix Credit , chain-of-custody number: CU-COC-807907).

Basis Weight	70 g/m <sup>2</sup>	ISO 536
Caliper	78 µm	ISO 534

### Adhesive

A general purpose permanent, acrylic based adhesive.

### Liner

Hygroflat 55, a one side coated, bleached kraft paper.

Basis Weight	55 g/m <sup>2</sup>	ISO 536
Caliper	58 µm	ISO 534

### Laminate

Total Caliper	152 µm±10%	ISO 534
---------------	------------	---------

### Performance data

Initial Tack	17 N/25mm	FTM 9 Glass
Peel Adhesion 90°	7 N/25mm	FTM 2 St.St.
Min. Application Temp.	0 °C	
Service temperature	-20°C to 80°C	

### Adhesive Performance

The adhesive is characterized by a high initial tack, excellent adhesion and good low temperature performance on a wide variety of substrates.

### Applications and use

This face material is designed for the manufacture of A4 sheets for use in laserprinters, copiers, monochrome inkjet and standard quality colour inkjet printers. The surface structure provides excellent toner bonding and print resolution.

The product is ideal for label applications using variable information such as address, instruction and inventory labels, labels for office use and many other applications.

### Conversion & printing

Facestock is suitable for simple line or process printing by flexo and offset.

The material can be converted by the conventional and high-speed wide format roll-to-sheet conversion technologies.

Suitable for edge stripping.

The Backing paper can be printed with conventional printing methods.

### Special Approvals


The adhesive complies with the European food directives and legislations, FDA 175.105 and the German recommendations XIV as published by BfR. BfR (Bundesinstitut für Risikobewertung) is the German Federal Institute for Risk Assessment. The adhesive can be used in direct contact with dry, non fatty foodstuffs.

### Shelf life

Two years under storage conditions as defined by FINAT (20-25°C; 40-50%RH)

## AE278

### Fasson® LCJ70 PREMIUM FSC - S2012HTC-HF55



LCJ70 PREMIUM FSC

S2012HTC

HF55

**Avery Dennison Materials Group Europe**

Lammenschansweg 140  
2321 JX Leiden  
The Netherlands  
+31 71 579 4100



This is an automatically generated datasheet. All data to be considered as typical values and subject to change without prior notice. Further testing is always recommended.

If you would like to make a suggestion or report a mistake on this datasheet, please send an email to [datasheet.mgmt@eu.averydennison.com](mailto:datasheet.mgmt@eu.averydennison.com)

**Warranty**

All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes.

Avery Dennison products are warranted to be free of defects in material or workmanship for a period of one year from the date of shipment. Should a defect be communicated to Avery Dennison within that time frame, Avery Dennison will evaluate and determine the existence of the defect and further decide, at its sole discretion, to either replace the defective product without charge or compensate it with a credit note in such amount as Avery Dennison deems reasonable. Avery Dennison shall have no responsibility beyond the replacement value of the defective product nor shall in any way be liable or responsible for consequential or incidental damages.

ANY OTHER WARRANTY, WHETHER EXPRESS OR IMPLIED, OR WHETHER OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR OTHERWISE, SHALL BE EXCLUDED. NO WAIVER, ALTERATION, ADDITION OR MODIFICATION OF THE FOREGOING CONDITIONS SHALL BE VALID UNLESS MADE IN WRITING AND SIGNED BY AN EXECUTIVE OFFICER OF AVERY DENNISON.

©2013 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.