

**AI399****Fasson ®****TRANSFER PET75 MATT  
WH - S8015-BG42WH**

## Key features

- > Good TT printability.
- > Very high resistance of TT print against harsh chemicals as used in the automotive industry.
- > High caliper polyester film used for covering holes and channels.

- > Solvent acrylic adhesive featuring high tack and peel adhesion on a wide variety of substrates, including low surface energy plastics. Suitable for labelling slightly rough surfaces.
- > UL and CSA recognised label material.

### Facestock

A white polyester film. The surface is covered with an absorbing, matt topcoat for very good ink anchorage.

Basis Weight	115 g/m <sup>2</sup>	ISO 536
Caliper	82 µm	ISO 534

### Adhesive

S8015 is a high strength permanent acrylic adhesive featuring high initial tack, adhesion and shear.

### Liner

BG42 white, a supercalendered glassine paper.

Basis Weight	64 g/m <sup>2</sup>	ISO 536
Caliper	57 µm	ISO 534
Transparency	50 %	DIN 53147

### Laminate

Total Caliper	165 µm±10%	ISO 534
---------------	------------	---------

### Performance data

Initial Tack	25 N/25mm	FTM 9 Glass
Min. Application Temp.	7 °C	
Service temperature	-40°C to 150°C	
Peel Adhesion 90°	14 N/25mm	FTM 2 st.st. 24hr
Adhesive Type	Solvent Acrylic	

### Adhesive Performance

The high tack, high coat weight adhesive S8015 is used for difficult substrates, including low surface energy plastics and coatings. It features high chemical and temperature resistance.

### Applications and use

Transfer PET 75 Matt White was specially developed for labels on Durables Goods, especially in the automotive industry. but also in other segments. Identification labels and logistical labels are the main applications. When printed with high quality thermal transfer ribbons very high chemical resistance of the print can be achieved.

This product is used when an adhesive combining high adhesion on difficult substrates combined with high chemical and temperature resistance is required. Typical application areas include labels in the automotive industry.

### Conversion & printing

Thanks to the special surface coating, very good results can be achieved with thermal transfer printers equipped with conventional or near-edge print heads and using either wax/resin or pure resin ribbons. In addition the product can also be printed by all conventional roll label techniques, such as flexo, UV letterpress, silkscreen. Specific testing is required. For easy diecutting sharp corners should be avoided.

### UL and CSA Recognitions



This product meets the requirements as stated in UL 969 and CSA C22.2 No. 0.15 for indoor use. The UL file number is MH27538.

### Shelf life

## AI399

## Fasson ®

### TRANSFER PET75 MATT WH - S8015-BG42WH



Two years under storage conditions as defined by FINAT (20-25°C; 40-50%RH)

All data to be considered as typical values and subject to change without prior notice. The actual front and liner used might influence adhesive values. Further testing is always recommended.  
If you would like to make a suggestion or comment on this datasheet, please send an email to [datasheet.mgmt@eu.averydennison.com](mailto:datasheet.mgmt@eu.averydennison.com)

### **Avery Dennison Materials Group Europe**

Willem Einthovenstraat 11  
2342 BH Oegstgeest  
The Netherlands  
+31 (0)85 000 2000

#### **Warranty**

All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>



©2019 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.