

Facestock

A matt white polyethylene film with a print-receptive topcoat.

Basis Weight	84 g/m ²	ISO 536
Caliper	82 µm	ISO 534

Adhesive

C3 is a transparent, dispersion-based removable, acrylic adhesive.

Liner

BG40 white, a supercalendered glassine paper.

Basis Weight	61 g/m ²	ISO 536
Caliper	54 µm	ISO 534

Laminate

Total Caliper	154 µm±10%	ISO 534
---------------	------------	---------

Performance data

Initial Tack	4 N/25mm	FTM 9 Glass
Peel Adhesion 90°	2.5 N/25mm	FTM 2 St.St.
Min. Application Temp.	0 °C	
Service temperature	-40°C to 100°C	

Adhesive Performance

C3 is a highly transparent adhesive with high ageing stability for removable labels, e.g. for cosmetics and pharmacy applications.

Applications and use

Applications are predominantly in home and personal care. Due to its flexibility the product is especially suitable for squeezable bottles and other flexible containers. The white, matt finished film blends well into matt plastic containers.

C3 removes clean from many substrates from polymeric (PET, PP, ABS, PS), fiberboard, aluminium, stainless steel, glass, window labelling (with limited outdoor UV exposure). Preliminary testing is recommended.

Conversion & printing

The matt topcoating can be printed by conventional printing techniques including flexo, screen, offset, letterpress, silkscreen, gravure, and hot or cold foiling processes. UV, water-based and solvent-based inks can be used. The topcoat is designed for optimum ink adhesion. On-press corona treatment is not advised. The face material is suitable for Thermal Transfer printing. Exact inks, foils and ribbons should be specified by your ink/foil/ribbon supplier.

Overvarnish is recommended if this product is used in applications where high scuff resistance is required.

Special Approvals

C3 complies with European food regulation 1935/2004/EC, with the German Recommendation (BfR) XIV and FDA 175.105. It also meets the demands of the limit values laid down in 10/2011/EU. In accordance with the requirements of relevant EU food regulations, the adhesive C3 may safely stand in direct contact dry, moist and such kind of fatty foodstuffs which have a reduction factor of at least 2 according to the Commission Regulation (EU) No 10/2011. This is based on migration results from testing in olive oil as simulant.


Shelf life

Two years under storage conditions as defined by FINAT (20-25°C; 40-50%RH)

AI458

Fasson®

PE85 TOP MATT WHITE - C3-BG40WH



PE85 TOP MATT WHITE

C3

BG40WH

This is an automatically generated datasheet. All data to be considered as typical values and subject to change without prior notice. Further testing is always recommended.

If you would like to make a suggestion or comment on this datasheet, please send an email to datasheet.mgmt@eu.averydennison.com

Avery Dennison Materials Group Europe

Willem Einthovenstraat 11
2342 BH Oegstgeest
The Netherlands
+31 (0)85 000 2000

Warranty

All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>



©2016 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.