

Facestock

A top coated aluminium foil, laminated to a white woodfree printing paper, with a bright silver finish.

| Basis Weight | 83 g/m² | ISO 536 |
|--------------|---------|---------|
| Caliper | 66 µm | ISO 534 |

Adhesive

A general purpose permanent, rubber based adhesive.

Liner

BG40 brown, a supercalendered glassine paper.

| 60 g/m² | ISO 536 |
|---------------|---|
| 51 µm | ISO 534 |
| | |
| 131 µm±10% | ISO 534 |
| | |
| 22 N/25mm | FTM 9 Glass |
| 11 N/25mm | FTM 2 St.St. |
| 0°C | |
| -40°C to 70°C | |
| | 51 μm 131 μm±10% 22 N/25mm 11 N/25mm 0 °C |

Adhesive Performance

The adhesive features excellent tack and adhesion on a wide variety of substrates, including apolar, slightly rough and curved substrates.

Particularly good performance at lower temperatures, e.g. labeling of chilled products.

Applications and use

Applications include high quality labels for cosmetic products, wine, spirits and premium product labelling. No show through from backprints.

Conversion & printing

Material has a print receptive topcoating in order to give good wettability and ink adhesion with suitable inks, may be printed using letterpress, screen, flexo, offset and gravure processes. Care with UV curing systems is required due to the reflective metal surface. Especially suitable for embossing. Metallised papers are sensitive to humidity and should not be exposed to extreme heat, cold or humidity as this may affect the printing performance and surface appearance.

Special Approvals


The adhesive complies with the European food directives and legislations, FDA 175.105 and the German recommendations XXI as published by BfR. BfR (Bundesinstitut für Risikobewertung) is the German Federal Institute for Risk Assessment. The adhesive can be used in direct contact with dry and moist, non fatty foodstuffs.

Shelf life

Two years under storage conditions as defined by FINAT (20- 25° C; 40- 50° RH)

AO432

Fasson ® BRIGHT FOIL SILVER - S2045N-BG40BR



BRIGHT FOIL SILVER

S2045N

BG40BR



Inspired Brands. Intelligent World."

Avery Dennison Materials Group Europe

Lammenschansweg 140 2321 JX Leiden The Netherlands +31 71 579 4100



This is an automatically generated datasheet. All data to be considered as typical values and subject to change without prior notice. Further testing is always recommended.

If you would like to make a suggestion or report a mistake on this datasheet, please send an email to datasheet.mgmt@eu.averydennison.com Warranty

All Avery Dennison statements, technical information and recommendations are based ANY OTHER WARRANTY, WHETHER EXPRESS OR IMPLIED, OR WHETHER OF on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR OTHERWISE, Dennison products are sold with the understanding that purchaser has independently SHALL BE EXCLUDED. NO WAIVER, ALTERATION, ADDITION OR MODIFICATION determined the suitability of such products for its purposes

Avery Dennison products are warranted to be free of defects in material or workmanship for a period of one year from the date of shipment. Should a defect be ©2013 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other communicated to Avery Dennison within that time frame, Avery Dennison will evaluate Avery Dennison brands, this publication, its content, product names and codes are and determine the existence of the defect and further decide, at its sole discretion, to owned by Avery Dennison Corporation. All other brands and product names are either replace the defective product without charge or compensate it with a credit note trademarks of their respective owners. This publication must not be used, copied or in such amount as Avery Dennison deems reasonable. Avery Dennison shall have no reproduced in whole or in part for any purposes other than marketing by Avery responsibility beyond the replacement value of the defective product nor shall in any Dennison. way be liable or responsible for consequential or incidental damages.

OF THE FOREGOING CONDITIONS SHALL BE VALID UNLESS MADE IN WRITING AND SIGNED BY AN EXECUTIVE OFFICER OF AVERY DENNISON.