

Facestock

A white, one side cast-coated mirror finished woodfree printing paper with a specific topcoating for excellent transfer and anchorage of ElectroInk as used in the Indigo process

Basis Weight 81 g/m² ISO 536

Caliper 73 µm ISO 534

Adhesive

A general purpose permanent, acrylic based adhesive.

Liner

BG40 brown, a supercalendered glassine paper.

Basis Weight 57 g/m² ISO 536

Caliper 51 µm ISO 534

Laminate

Total Caliper 138 µm±10% ISO 534

Performance data

Initial Tack 15 N/25mm FTM 9 Glass

Peel Adhesion 90° 8 N/25mm FTM 2 St.St.

Min. Application Temp. 5 °C

Service temperature -20°C to 80°C

Adhesive Performance

The adhesive is characterized by a high initial tack, excellent adhesion and good low temperature performance on a wide variety of substrates.

Applications and use

The product is used in a variety of labelling applications, when the advantages of digital printing: short runs, last minute changes, personalised layouts and fast turn-round full colour printing are required.

Conversion & printing

The topcoating ensures full transfer of ElectroInk in the one-shot transfer step in the HP Indigo press and related engines. The coating also provides excellent image quality and ink anchorage of ElectroInk based images. Print quality in conventional processes and combination with laquers to be evaluated. Excellent conversion characteristics in rotary and flat-bed. It is recommended to overvarnish or overlamine the product to protect the print.

Special Approvals

The adhesive complies with the European food directives and legislations, FDA 175.105 and the German recommendations XIV as published by BfR. BfR (Bundesinstitut für Risikobewertung) is the German Federal Institute for Risk Assessment. The adhesive side may stand in direct contact with dry, moist and such fatty foodstuffs which have a correction factor of at least 3 according to the Regulation (EU) No 10/2011.


Shelf life

One year under storage conditions as defined by FINAT (20-25°C; 40-50%RH)

AQ211

Fasson®

**DIG INDI HGW PREMIUM TOP -
S2000N-BG40BR**



DIG INDI HGW PREMIUM
TOP

S2000N

BG40BR

This is an automatically generated datasheet. All data to be considered as typical values and subject to change without prior notice. Further testing is always recommended.

If you would like to make a suggestion or comment on this datasheet, please send an email to datasheet.mgmt@eu.averydennison.com

Avery Dennison Materials Group Europe

Willem Einthovenstraat 11
2342 BH Oegstgeest

The Netherlands
+31 (0)85 000 2000



Warranty

All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>

©2016 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.