

Facestock

A matt, white paper with good opacity, absorption and toner bonding characteristics.

The facestock is made with FSC certified pulp (FSC Mix Credit , chain-of-custody number: CU-COC-807907).

Basis Weight	67 g/m ²	ISO 536
Caliper	77 µm	ISO 534

Adhesive

A general purpose permanent, acrylic based adhesive.

Liner

Hygroflat 52, a one side coated, bleached kraft paper.

Basis Weight	51 g/m ²	ISO 536
Caliper	54 µm	ISO 534
Transparency	48 %	ISO 534

Laminate

Total Caliper	151 µm±10%	ISO 534
---------------	------------	---------

Performance data

Initial Tack	9 N/25mm	FTM 9 Glass
Peel Adhesion 90°	5 N/25mm	FTM 2 St.St.
Min. Application Temp.	0 °C	
Service temperature	-20°C to 80°C	

Applications and use

This face material is designed for the manufacture of A4 sheets for use in laserprinters, copiers, monochrome inkjet and standard quality colour inkjet printers. The surface structure provides good toner bonding and print resolution.

The product is ideal for label applications using variable information such as address, instruction and inventory labels, labels for office use and many other applications.

Conversion & printing

Facestock is suitable for the conversion to A4 sheets with simple process printing by flexo and offset.

The material can be converted by the conventional roll-to-sheet conversion technologies -specifically "Butt-cut" formats.

Special Approvals

The adhesive complies with the European food directives and legislations, FDA 175.105 and the German recommendations XIV as published by BfR. BfR (Bundesinstitut für Risikobewertung) is the German Federal Institute for Risk Assessment. The adhesive can be used in direct contact with dry and moist, non fatty foodstuffs.


Shelf life

Two years under storage conditions as defined by FINAT (20-25°C; 40-50%RH)

aw389

Fasson®

LCJ BASIC FSC - S2012-HF52



LCJ BASIC FSC

S2012

HF52

This is an automatically generated datasheet. All data to be considered as typical values and subject to change without prior notice. Further testing is always recommended.

If you would like to make a suggestion or comment on this datasheet, please send an email to datasheet.mgmt@eu.averydennison.com

Avery Dennison Materials Group Europe

Willem Einthovenstraat 11
2342 BH Oegstgeest
The Netherlands
+31 (0)85 000 2000

Warranty

All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes.



ANY OTHER WARRANTY, WHETHER EXPRESS OR IMPLIED, OR WHETHER OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR OTHERWISE, SHALL BE EXCLUDED. NO WAIVER, ALTERATION, ADDITION OR MODIFICATION OF THE FOREGOING CONDITIONS SHALL BE VALID UNLESS MADE IN WRITING



Inspired Brands.
Intelligent World.™

Avery Dennison products are warranted to be free of defects in material or workmanship for a period of one year from the date of shipment. Should a defect be communicated to Avery Dennison within that time frame, Avery Dennison will evaluate and determine the existence of the defect and further decide, at its sole discretion, to either replace the defective product without charge or compensate it with a credit note in such amount as Avery Dennison deems reasonable. Avery Dennison shall have no responsibility beyond the replacement value of the defective product nor shall in any way be liable or responsible for consequential or incidental damages.

AND SIGNED BY AN EXECUTIVE OFFICER OF AVERY DENNISON.

©2013 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.